

SMILSignage Display10

Widescreen Wi-Fi Network Display with Touch Button Input



Highlights

- All-in-one signboard with Touch Buttons
- Plug-and-play professional signage
- Works with your management solution

Suitable for

- In-store promotion
- Interior décor integration
- Interactive video display
- Museum and library information



The SMIL-Signboard 10 is a Widescreen, all-in-one digital signage display with Touch Button input.

All-in-one signboard with Touch Buttons

The SMIL-Signboard 10 deliver DVD quality video content in a compact frame you can place anywhere. The sleek unit integrates the media player, highbrightness display, expandable local storage, and wireless network for easy placement. Since the power adapter cable is the only physical connection to the player, it's easy to achieve a clean and professional

presentation in tight spaces. 4 programmable touch buttons provide interactive features, letting users discover promotional materials, skip to content of interest, and drill down information. Plug-and-play professional signage The SMIL-Signboard 10 is engineered for troublefree, plug-and-play professional digital signage. A Watchdog timer lets the player recover and resume playback from power, network, or other disruptions. The all metal enclosure provides reliable passive cooling and features screw-lock connectors to prevent loose cables. Covered SD card slot lets you expand beyond the 2 GBs of built-in solid-state local storage while protecting contents. Enjoy all the benefits of an industrial PC (IPC) Without the cost and uncertainty of complex, multi-purpose systems. Works with your management solution SMIL-Player's SMIL open standard players offer a new class of dedicated hardware that works with your existing management solution. SMIL-Player works with leading signage companies to provide a repertoire of connected signage hardware, be it shelf-top 10" digital signboards, audio players, HD poster displays, or Blu-ray-quality HD video appliances. Developers can also leverage W3C SMIL (Synchronized Multimedia Integration Language) compatibility across various SMIL based signage appliances to meet project-specific budgets and changing criteria.



Technical Specifications

Screen Media Standards Support

Image: JPEG baseline, up to 12 megapixels Audio: MPEG L2 or MP3, up to 320Kbps Video: MPEG-1 or MPEG-4 ASP, 2Mbps (720x400 resolution 16:9 content recommended) NOTE: MPEG 2 video is NOT supported

Digital Signage Features

Auto-play starts playing scheduled contents automatically when power is re-established. Automatic error recovery with built-in WDT. Real-time clock keeps time for up to 1 year unplugged. Automafic NTP keeps time and date in sync.

Playback Control

Programmable 4-button touch controls W3C SMIL 3.0 instructions (sub-set) Real-time clock playlist events Network playlist sync USB direct sync

Content Management

Manager Express starter utility 3rd party solution (optional license)

Display and Sound

10.1" TFT LCD Wide aspect ratio
300 nits maximum brightness
800 x 480 native resolution
Built-in stereo speakers 2Wx2
Mounting Options
Built-in VESA compatible
75 x 75(mm) posts
Local Storage
Internal 2 GB local storage (approx. 120 minutes of maximum quality video @2Mbps or thousands of still images).
Memory card slot: Secure Digital (SD/SDHC). Card capacity: Up to 8 GB (SDHC)

Network Connectivity and I/O Ports

Wi-Fi: IEEE 802.11 b/g

Wi-Fi Security: WPA/WPA2, TKIP/AES Ethernet: R145 Port via USB dongle (option) USB storage host (Type A) 3.5 mm stereo audio out jack Supplied Accessories Software CD Quick start quide

Quick start guide AC power adapter

Optional Accessories

USB to RJ45 Ethemet adapter Power supply

Rating: 12V 1.5A

UL/CE/PSE certified power supplies Interchangeable connector system includes US and European plugs, optional UK plug *prelim.

Environmental

Operating temperature: 0 to 40°C Humidity: 5 to 85% @ 40°C, non-condensing

Dimensions (WxHxD)

Main unit: 271 x 185 x 29mm 10.6" x 7.28" x 1.14"

Weight

700 grams/ 1.5 pounds

Certifications

CE/FCC/RoHS Warranty 1-year limited parts & labor







Sirkom Europe, S.L. Avda. Lendakari Aguirre, 50-52 – 48014 Bilbao (Spain) Tel. +34 944765344 marketing@sirkom.com

www.sirkom.com