



ProLite T1732MSC

The ProLite T1732MSC 17" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Menu Buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the TouchScreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours. Analogue and DVI inputs are available for flexible connectivity along with USB for the Touch Interface. The multi-touch function is supported only under Windows® 7 and 8.

DISPLAY CHARACTERISTICS

| | |
|---------------------|--|
| Diagonal | 17" |
| Touchtechnology | projective capacitive, multitouch (2 compatible touch points - supported only under Windows® 7/8), activated by finger |
| Panel | TN |
| Glass hardness | 7H minimum |
| Display area h x w | 270.5 x 338 mm; 10.6" x 13.3" |
| Response time | 5 ms |
| Contrast | 1 000 : 1 with touch panel |
| Brightness | 225 cd/m² with touch panel |
| Viewing zone | horizontal/vertical: 160° / 160°; right/left: 80° / 80°; up/down: 80° / 80° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.264 x 0.264 mm |
| Native resolution | 1280 x 1024 (1.3 megapixel) |
| Horizontal sync | 31,4 - 80 KHz |
| Vertical sync | 56 - 75 Hz |
| Synchronization | Separate Sync |
| Aspect ratio | 5 : 4 |
| Light transmittance | 90% |

POWER MANAGEMENT

| | |
|-------------------|---|
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | 25 W typical; max. 2 W in Power management mode |
| Power management | VESA DPMS |

DIMENSIONS & WEIGHT

| | |
|----------------------|--------------------|
| Dimensions w x h x d | 387 x 342 x 202 mm |
| Weight | 5.6 kg |

INTERFACES & CONNECTORS

| | |
|-------------------------|------------------------------|
| Analog input connector | VGA (D-Sub) |
| Digital input connector | DVI-D |
| Inputs | USB (for touch connectivity) |

SPECIAL FEATURES

| | |
|-------------------|--|
| Controls | On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power) |
| User controls | contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute |
| Speakers | 2 x 1 W (Stereo) |
| Anti-theft-device | Kensington-lock™ prepared |
| Safety | CE, TÜV/Bauart, VCCI, CB, CU, IP54 |
| Tilt angle | 90° up; 5° down |
| VESA mounting | 100 x 100 mm |
| Colour | Black, White |

ACCESSORIES

| | |
|----------------------|---|
| Driver | multi-touch: Windows7/8 (HID compliant), single-touch: Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX) |
| Included accessories | power cable, VGA (D-Sub) signal cable, DVI-D signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), screw, quick start guide, safety guide |