

## ProLite E2278HD



The ProLite E2278HD is a 22" FHD 1920x1080 LED-backlit monitor. It features 5msec response time and >5M: 1 Advanced Contrast Ratio assuring vibrant images and blur free Video. Analogue VGA and Digital DVI inputs ensure compatibility with the latest systems and associated graphics cards. The monitor is Energy Star qualified and VESA mount compatible. A reliable solution for both home and office use.

### DISPLAY CHARACTERISTICS

Diagonal	21.5"
Panel	TN LED-backlit
Display area h x w	268.1 x 476.6 mm; 10.6" x 18.8"
Response time	5 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	300 cd/m <sup>2</sup> max.
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9

### POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	19 W typical; max. 0.3 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

### EPEAT SILVER

<b>EPEAT</b>	EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit <a href="http://www.epeat.net">www.epeat.net</a> for the registration status in your country.
--------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### DIMENSIONS & WEIGHT

Dimensions w x h x d	514.5 x 369.5 x 177.5 mm
Weight	2.8 kg

### INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D
HDCP	yes
	D-Sub, DVI-D

### SPECIAL FEATURES

<b>Apple - Mac</b>	All iiyama monitors are compatible with Apple-Macintosh computers.
<b>Controls</b>	On-Screen-Display in 10 languages (EN, FR, DE, IT, PL, ES, NL, JP, Chinese, RU) and 6 front controls (Power, Menu/ Select, +/- Brightness, -/ ECO, Exit, Auto)
<b>User controls</b>	auto adjust, luminance (brightness, contrast), geometry (H. position, V. position, clock, phase), colour, OSD (H. position, V. position, timeout), language, recall, miscellaneous (sharpness, DDC/CI, display information, ACR, display mode, opening logo), input select
<b>Anti-theft-device</b>	Kensington-lock™ prepared
<b>Safety</b>	CE, TUV-Bauart, VCCI-B, CU
<b>Tilt angle</b>	23° up; 5° down
<b>VESA mounting</b>	100 x 100 mm
<b>Colour</b>	Black

### ACCESSORIES

<b>Driver</b>	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
<b>Included accessories</b>	power cable, VGA (D-Sub) cable, DVI-D cable, stand-base, quick start guide, safety guide