



ProLite GB2773HS

27" pro-gamer monitor with 144Hz refresh rate

Through all stages: concept, design and development - the ProLite GB2773HS was meant to be a real game changer giving true hardcore gamers the competitive edge they need to make split second decisions. Smooth and judder free graphics during fast paced games are guaranteed by the use of a high quality 144Hz panel with a blistering 1ms response time. Ergonomic, height adjustable stand allows you to easily adjust the screen position to your preferences. A truly amazing gaming experience.

DISPLAY CHARACTERISTICS

Diagonal	27"
Panel	TN LED
Display area h x w	336.3 x 597.9 mm; 13.2" x 23.5"
Response time	1 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	300 cd/m² typical
Viewing zone	horizontal/vertical: 170°/ 160°; right/left: 85°/ 85°; up/down: 80°/ 80°
Display colour	16.7 million
Pixel pitch h x v	0.311 x 0.311 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	DVI: 30 - 159 KHz
Vertical sync	DVI: 55 - 144 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9

POWER MANAGEMENT

Power Supply Unit	internal			
Power usage	35 W typical; max. 0.5 W in Power management mode			
Power management	VESA DPMS, ENERGY STAR®			
DIMENSIONS & WEIGHT				
Dimensions w x h x d	647 x 415.5 (522.5) x 230 mm			
Weight	7.4 kg			

Power supply AC 100 - 240 V, 50 / 60 Hz

INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D, HDMI
HDCP	yes
Headphone connector	Yes
Output connector	headphone socket
	D-Sub DVI-D HDMI

SPECIAL FEATURES	
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2B™
Controls	Via OSD in 8 languages (EN, DE, FR, ES, IT, FIN, Chinese, JP) and 5 front controls (Power, Select/ Input Select, Scroll up/ Audio , Scroll down/ i-Style Colour, Menu)
User controls	auto adjust, picture adjust (contrast, brightness, ACR, ECO, OD), input select, audio adjust (volume, mute, HDMI audio), colour adjust, information, manual image adjust (clock, H/V position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, opening logo, LED), memory recall
Speakers	2 x 2.5 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Certificates	CE, TÜV-Bauart, GOST-R
Height adjustable stand	Yes
Height adjustment	107 mm
Swivel Stand	90°; 45° left; 45° right
Tilt angle	17° up; ° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Dr	river	Windows 95 / 98 / 2000 / ME / XP / Vista/ 7/ 8
Included accesso	ries	power cable, DVI-D cable (dual-link), HDMI cable, audio cable, stand, quick start guide,

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.