

## Focus Firestore FS-H200PRO - Specifications

- Display: 2.5 inch (diagonal) colour TFT display  
320 x 240 pixel resolution
- Input/Outputs: DV I/O: 25Mbps  
HDV I/O: MPEG-2 transport stream (19.8 or 25 Mbps)  
Computer I/F: USB 2.0 (up to 48- Mbps) (1 x USB-A female)  
Video I/O: 1 x 6-pin IEEE 1394 (FireWire/i.LINK)  
RS-232C control: 1 x 2.5mm minijack
- Audio DV input: Embedded 2-channel (48 kHz, 16-bit) or 4-channel (32 kHz, 12-bit)  
NOTE: 4-channel (32 kHz, 12-bit) audio is supported only in DTE Technology with RawDV file format  
HDV input: Embedded MPEG-1 Audio Layer II
- Video (DV): 25 Mbps; 8-bit 4:1:1 (NTSC-DV) or 4:2:0 (PAL-DV) (model dependent)
- Video (HDV): MPEG-2 (MP@H-14), 4:2:0, 720p (8-bit, 19.7 Mbps) or 1080i (8-bit, 25Mbps)
- DTE Formats (HD): .m2t 720p 24/25/30/50/60  
.m2t 1080i 50/60  
QuickTime 1080i 50/60  
QuickTime 720p 30  
MXF 1080i 50/60  
MXF 720p 30
- DTE Formats (SD): AVI Type 1  
AVI Type 2 | AVI Type 2 24p  
QuickTime | QuickTime 24p  
Canopus AVI  
Matrox AVI  
RawDV
- Timecode: DV embedded timecode (drop or nondrop)
- Compact Flash Compatibility: Records to industry-standard Compact Flash (CF) Type I cards, rated at minimum 30MB/s write speed.
- Qualified CF Cards: SanDisk Extreme Pro 64GB (90MB/s) SDCFXP-064G-A91  
SanDisk Extreme Pro 32GB (90MB/s) SDCFXP-032G-A91  
SanDisk Extreme Pro 16GB (90MB/s) SDCFXP-016G-A91  
SanDisk Extreme 64GB (60MB/s) SDCFX-064G-A61  
SanDisk Extreme 32GB (60MB/s) SDCFX-032G-A61  
SanDisk Extreme 16GB (60MB/s) SDCFX-016G-A61  
SanDisk Extreme 8GB (60MB/s) SDCFX-008G-A61  
SanDisk Extreme IV 16GB SDCFX4-016G-901  
Transcend 600X 32GB (90MB/s) TS32GCF600  
Transcend 400X 64GB (90MB/s) TS64GCF400
- Notes on Compatibility: Please check with the CF manufacturer for up-to-date Part Numbers as changes may have occurred.
- Disk Format: UDF (Universal Disk Format) or FAT32 (user selectable)
- OS Compatibility: Windows XP, Vista, Windows 7, MAC OS X
- Power Adapter: 11 - 18V DC; minijack power connector
- Battery: Custom removable Li-ion rechargeable battery
- Battery Capacity: Standard capacity battery (180 minutes)
- Dimensions: 70 x 137 x 23 mm
- Weight: 0.34 kg
- Compliance: CE, C-Tick, FCC, and RoHS
- Warranty: 1 year
- Models: NTSC or PAL models available  
(PAL model ordered unless you state in the comments you want otherwise)