

## Focus Firestore FS-T1001 Specifications

|                      |   |
|----------------------|---|
| Display              | 2.4 inch (diagonal) color OLED display<br>320 x 240 pixel resolution  |
| Input/Output         | HD-SDI (1 x BNC); SMPTE 292M with embedded audio  |
| Audio                | 2- or 4-channel (48kHz, 16-bit) linear PCM<br>NOTE: 4-channel audio applies to HQ mode only   |
| Video Codec          | Long GOP MPEG-2 (4:2:0)<br>HQ Mode: MPEG-2 (MP@H-14), VBR (35 Mbps max.)<br>SP Mode: MPEG-2 (MP@H-14), CBR (25Mbps)   |
| Timecode             | HD-SDI embedded timecode (SMPTE RP 188)   |
| Frame Rates          | <b>HQ Mode:</b><br>1920 x 1080 59.94i/50i/29.97P/25P/23.98P<br>1440 x 1080 59.94i/50i/29.97P/25P/23.98P<br>1280 x 720 59.94P/50P<br><b>SP Mode:</b><br>1440 x 1080 59.94i/50i |
| Media                | Slot: 1 x SxS with polymer dust cover<br>Memory Cards: SxS Pro (Express 34)<br>Accommodates a Sony MEAD-SD01 adapter for emergency backup                                     |
| Media Format         | FAT32   |
| USB                  | 2 x USB 2.0 Type A (host or device mode)  |
| OS Compatibility     | Windows XP, Vista, Windows 7; Mac OS X  |
| Power Adapter        | 4-pin XLR   |
| Power Requirement    | 11 - 18V DC; Power Consumption: <10W  |
| Battery              | 14.4V Sony BP-L Mount   |
| Dimensions           | 2.5" wide x 7.25" high x 5.75" deep (63.5mm x 184mm x 146mm)  |
| Weight               | 2.67 lb. (1.21 kg)  |
| Compliance           | CE,C-Tick, FCC Class A, and VCCI  |
| Warranty             | 1 year  |
| Accessories Included | 75-Ohm BNC cable, USB A-to-A cable  |
| Optional Accessories | 75-Ohm BNC cable, USB A-to-A cable  |