



VIDA CENTER

WELCOME TO VIDA CENTER **2:52 p.m.**

HAIR & MAKEUP SHOW
saturday and sunday

SPLASH.
FASHION BOUTIQUE
\$4.99
Variety of styles available!

Vincenzo
MENSWEAR
NOW HIRING
see store manager for details

OTHER'S DAY SPECIAL GIFTS PRICED FROM \$25 AT STROMS › AUTHOR JEAN SIMON BOOK \$

LG SOURCE MENU AUGUST 0/1

Panel
 Screen Size 42"
 Aspect Ratio 16 : 9
 Native Resolution 1920 x 1080(WUXGA)
 Pixels(H x V x 3) 6 220 800
 Brightness 500cd/m2
 Panel type Transreflective. Brightness eq to 1500cd/m2 in direct sun light.
 Contrast Ratio @ 5lux 3000:1
 Contrast Ratio @ 4000lux 400:1
 Viewing Angle(H x V) 178 x 178
 Color Depth 10.6 Billion
 Response Time 9 ms(G to G)
 Surface Treatment Hard Coating(3H)
 MTBF 50,000 Hr., Portrait&Landscape

VIDEO
 Max Input Resolution 1920 X 1080@ 60Hz(RGB, HDMI/DVI)
 Recommended Resolution 1920 X 1080 @ 60Hz(RGB, HDMI/DVI)
 H-Scanning Frequency 30 ~ 83kHz (RGB, HDMI/DVI)
 V-Scanning Frequency 56 ~ 75 Hz(RGB), 60 Hz(HDMI/DVI)
 Pixel Frequency 148.5 MHz(RGB, HDMI/DVI)
 Sync Compatibility Separate / Composite / Digital
 Video Input RGB, HDMI/DVI
 Picture mode Vivid / Standard / Cinema / Sports / Game / User1 / User2
 Color temperature Warm / Medium / Cool / User

REAR INPUTS
 Component Video 1 Hi-Res
 PC Input 15-Pin D-Sub 1 / 1 (Input/Output)
 Composite Video 1 / 1 (Input/Output)
 Audio Output 1
 Audio Inputs 2 Plus PC Sound
 HDTV Formats Component : 720p / 1080i / 1080P
 HDMI 720P / 1080i / 1080p
 PC Formats Auto Scaling to WUXGA
 HDMI/DVI with HDCP Yes
 RS-232C 1 / 1 (Input/Output) Female-to- Female Crossed Type
 RJ-45 Yes
 S-Video 1 (S-Video has a priority but there is no input mode.)
 Audio Jack Yes
 Discrete IR Input Yes
 External_Speaker Out Yes

AUDIO
 Auto Volume Yes
 Balance Yes
 Audio Power 20W (10W x 2)
 Speaker On/off Yes
 Sound mode Clear Voice / Standard / Music / Cinema / Sports / Game / User

SPECIAL FEATURES

Advanced Picture In Picture No
 New Temperature Sensor Yes
 New Split Zoom 5 x 5 Self Video Wall, supports natural mode
 Image Zoom No
 Source Selection Digital(HDMI/DVI) / Analog(RGB) / Component / AV
 Display control through Network Yes
 Brightness/Contrast Yes
 Color Warm / Medium / Cool / User Control(R/G/B)
 Position H / V
 Tracking Auto / Clock / Phase
 Set-up Language(English/French/Spanish/Italian/German/Portugues/Korean/Japanese/Chinese/Russian)
 ISM Method Normal/White washy/Orbiter/Inversion/Dot wash
 Advanced Gamma / Film mode / Black level / Noise Reduction
 Time Clock / On/off timer / Auto sleep / Power on Delay
 Information display Serial Number, SET ID, MNT S/W Version, LAN S/W Version
 Mute Yes
 Sleep Timer Yes
 Auto Power/Source Memory Yes
 Key Lock Yes
 DPM Select Yes

CABINET

Color Black
 Monitor Dimension (W x H x D) 38.07" X 22.04" X 4.87"
 Weight (head) 41.24 lb
 Monitor with Optional Stand Dimensions (W x H x D) 38.07" X 25.0" X 10.18"
 Weight (head+stand) 44.14lb
 Monitor with Optional Stand & Speaker Dimensions (W x H x D) 38.07" X 25.0" X 10.18"
 Weight (head+stand+speaker) 45.84 lb
 Carton Dimensions (W x H x D) 42.09 X 25.9 X 7.0 (full package)
 Packed Weight 38.07 x 22.05 x 4.88 (head only)
 VESATM Standard Mount Interface 52.5lb
 47.96lb
 600 x 400

POWER

Power Supply 100-240V~, 50/60Hz
 Power Type Built-in Power
 Power Switch Type Tact Switch
 Power Saving Normal
 Stand-by/Suspend 220 W
 DPM Off 2W(RGB), 4W(HDMI)
 Switch Off 2W(RGB), 4W(HDMI)
 1W

STANDARD(CERTIFICATION)

Safety UL / c-UL / CB scheme / TUV / NEMKO
 EMC FCC Class "B" / VCCI / C-tick / CE / MIC

