

## SRK-070-1

### ADVERTISING DISPLAY (Panel Digital 7" con Player integrado)



## CARACTERISTICAS

- Supports multiple file formats: MP3, WMA, JPG, MPEG-1, MPEG-2, MPEG-4, VOB
- Supports CF/SD(High-speed), MMC/USB 2.0(Hot plug).
- Single repeat, All repeat.
- Auto-play when turned on with the cards/USB inserted; Supports 16 kinds of auto play
- Display mode: 4:3 / 16:9 (modificable)
- BGM mode (Auto-boot mode can be set): Support background music
- Pictures can be rotated 90°( Vertical display)
- Super time switch function, can auto turn on/off at a specific time
- One key copy; PC link is available
- Picture Display Time: Picture Display Time is modifiable
- Time Display: Time Display or not is modifiable
- Full function remote control, easy operation
- Multi-Language OSD: Chinese, English, Japanese, French, German, Danish, Spanish
- Product color: Pearl white, blue, black etc
- Accessories: Remote control(optional), instruction manual, AC adapter, bracket(optional)

## ESPECIFICACIONES:

### Display

LCD size:	7 inch (Diagonal)
Display area:	154.0x86.6mm 16:9
Resolution:	800*3(RGB)(W) X 480(H) (digital panel)
Pixel Pitch:	0.0642(W) × 0.1790(H) mm
Luminance:	250cd/m <sup>2</sup>
Contrast Ratio:	500:1
Viewing Angle:	+70/-70 (H), +50/-70(V) (degree)
Response Time:	10ms
Display mode Optional	16:9 / 4:3
MTBF	50,000 (hours)

### I/O

AC Power Input:	AC: 100~240 V
DC Power Output:	12V / 1.5A
Integrated Speakers:	2W x 2
IR Remote:	Yes
Menu OSD:	Yes

### Card reader

Interface:	CF/MMC/SD/USB(2.0)
Photo:	JPEG, BMP
Video:	MPEG 1, MPEG 2, MPEG 4, AVI, MP4, VOB
Audio	MP3, WMA

### Mechanical and Environmental

Operating temperature:	0°C~ 40°C (32°F~104°F)
Storage temperature:	-20°C ~60°C (-4°F~140°F)
Storage humidity:	10% ~ 95%@40°C,Non-condensing
External Colors:	Pearl white (other colors available, but MOQ: 200PCS)
Vibration:	10 ~ 150Hz, 0.15mm 10 cycles 1G
Shock:	30G peak acceleration (11 msec. duration)
Dimensions (L*W*H):	216.8 x 104.8 x 28mm non-include wall bracket

### Accessories

Wall bracket:	Magnetic Bracket (Optional)(VESA 75mm/10 holes)
Remote control:	Yes (Infrared Remote) (Optional)
AC adapter:	Yes

### Packing

Package:	10 PCS/CTN
Packaging Size/pcs:	28×26×10 cm (small white box)
Carton Size/10 pcs.	59.5×54×27.5 cm (carton)
Gross Weight:	1.5 kg/pcs

### Conformity

Conformity:	CE, FCC, ROHS
Warranty:	1 Year