

NMP-530

**NETWORK MEDIA PLAYER
FOR DIGITAL SIGNAGE/
NARROWCASTING APPLICATIONS**

Dynamic Digital Signage

ViewSonic's NMP-530 Network Media Player turns any display into a digital signage display. It's an IP-based media player with MPEG-1/2/4 video stream capability for digital signage applications. The NMP-530 replaces remote PCs. It's small and lightweight, yet powerful enough for digital signage applications in hotels, restaurants, retail stores, arenas, stadiums, transportation centres, schools, financial institutions and manufacturing. The powerful processor delivers smooth playback of high-definition video and Flash® content. The NMP-530 is equipped to handle many layers of high-quality graphics, text, and video and is a cost-effective solution. From Macromedia Flash to HTML and from video to still pictures, with the incorporated Cisco ACNS and IPTV platforms, the ViewSonic NMP-530 allows pain-free client integration within existing network solutions.

MAKE YOUR MESSAGE COME ALIVE

> Local storage

2GB of native storage and USB ports allow more content downloads during non-peak network hours

> Network ready for easy installation

Easily integrates into existing networks without replacing or reconfiguring existing infrastructure. Supports a wide variety of digital display components and multi-vendor networks.

> Easy audio and video streaming with content-rich video and graphics

Display dynamic and captivating content with the included Macromedia® Flash® 6 Player. NMP-530 Media players function well with UDP & RTP based encoders supporting constant and various bit rates, displaying excellent quality mpeg-1, mpeg-2 and mpeg-4 (encapsulated in mpeg-2 transport) streams. Flexible display modes enable you to show content in landscape or portrait mode, and in single or multiple zones on each display within the network.

> Web-based user interface and built-in browser

Allows changes to network, video and browser settings, even firmware upgrades through the media player. The built-in Mozilla browser lets users render any HTML content and play Macromedia® Flash® applications.

> Lower total cost of ownership (TCO)

Eliminates local/remote PCs. Offers simplified cabling and installation plus easy-to-use GUI software.

> Easy, flexible device management

Remotely manage display and network information through the user-friendly web interface, Telnet, ViewSonic Administration Server or Cisco management software. Fully integrated with Cisco ACNS and IPTV platforms, the NMP-530 Media Player allows pain-free client integration within existing Cisco solutions.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic recommends our VX2835wm, CD3200-E, CD4210, CD4620 or any ViewSonic large screen LCD monitor or LCD TV for use with the NMP-530 to give you the best possible digital signage results.

ViewSonic®
See the difference™ 

NMP-530

NETWORK MEDIA PLAYER FOR DIGITAL SIGNAGE APPLICATIONS



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

OPERATING SYSTEM		Linux
SUPPORTING PROTOCOLS		TCP/IP, HTTP
INSTALLED SOFTWARE		Web browser with Flash® plug-in, standalone Flash® player, HD media player
NETWORK MANAGEMENT		ViewSonic Administrative Server (VAS), Web-based, Telnet, TAs, Cisco ACNS supported
CONNECTOR	Digital	1 x HDMI
	S-Video/Component	1 x mini DIN jack (for Y/C and YPbPr)
	Composite	1 x RCA jack (CVBS)
	Audio	1 x RCA set L/R
	USB	1 x USB (4-pin Typ A)
	I/O	1 x RS-232
	Network	1 x RJ45 (10/100 Ethernet)
	Power	1 x DC-in jack
LOCAL STORAGE/ MEMORY	SD card	2GB (intergrated)
	RAM	128MB
	Flash	64MB
DECODING FORMAT	Video	MPEG-1,2,4, Macromedia® Flash®
	Audio	MPEG-1 (layers 1&2), MP3, WAV, Dolby AC-3 pass through
STREAMING PROTOCOL	Types	HTTP, UDP, VDP, RTP, IP/TV, local file playback
RESOLUTIONS		640 x 480, 800 x 600, 1024 x 768, 1280 x 1024, 1280 x 768, 1360 x 768
VIDEO FORMAT		SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i)
IMAGE FORMAT		JPEG, PNG
SCREEN ROTATION		Landscape, portrait (+90°/-90°)
POWER	Voltage	AC 100-240V universal power adapter: output DC 5V (max.)
OPERATING CONDITIONS	Temperature	10°-40°C
	Humidity	20%-85% (non-condensing)
DIMENSIONS	W x H x D mm	178 x 130 x 25 (physical)
WEIGHT	Net/Gross	0.45kg/0.77kg
REGULATIONS		CE, CB, UL, cUL, FCC, Part 15 Class B, RoHS, BSMI, RSB (for power adapter only)
PACKAGE CONTENTS		Media player, remote control with batteries, AC adapter, S-video-component adapter, Ethernet cable, RS232 cable, Quick Start Guide, User Guide on CD

Single platform. Many uses...
Leverage your investment to the fullest.



Corporate Messaging



Promotion



Billboard



Encoding

Management

Distribution

Training



Any Audio or Video



Security



ViewSonic Europe Limited/UK Tel: +44 (0) 207 921 2200
ViewSonic Germany Tel: +49 (0) 21 54 91 88 0
ViewSonic France Tel: +33 (0) 1 41 47 49 00
ViewSonic Corporation Tel: +1 909 869 7976
ViewSonic Belux Tel: +32 (0)56 85 26 27

ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 20 7120 860
ViewSonic Italy Tel: +39 02 73 95 50 22
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands Tel: +31 (0)20 491 9254

ViewSonic Norway Tel: +47 (0) 22 88 16 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

Specifications subject to change without notice. Selection, offers and programmes may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. NMP-530-1 06/07-UK