

## ProLite LE4262S



ProLite LE4262S is a 42" Full HD professional, feature-rich and robust large format display. Incorporating the latest IPS panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering exceptional performance with the added benefit of saving on power. The display supports PIP function. A wide range of video and audio inputs ensures compatibility with multiple platforms. ProLite LE4262S is VESA mountable and has a special space at the rear for mounting a small PC or a multimedia player. The OSD can be controlled with both control buttons and an included remote control. This display will suit a massive range of applications including public signage, retail, exhibitions and conference centres, POS/POI, control rooms, and production facilities.

### DISPLAY CHARACTERISTICS

Diagonal	42"
Panel	IPS
Display area h x w	523.26 x 930.24 mm; 20.6" x 36.6"
Response time	5 ms
Contrast	1 500 : 1 typical
Contrast	4 250 : 1 ACR
Brightness	500 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Pixel pitch h x v	0.4845 x 0.4845 mm
Native resolution	Full HD 1080p, 1920 x 1080 ( 2.1 megapixel)
Horizontal sync	23 - 92 KHz
Vertical sync	56 - 85 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Display colours	1,07G colours (10-bit)
PIP (Picture in Picture)	large, medium, small
Max. non-stop operating time	20 hours/day (IRFM on)

### POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	210 W typical; max. 1 W in Power management mode
Power management	VESA DPMS

### DIMENSIONS & WEIGHT

Dimensions w x h x d	992 x 585 x 119.5 mm
Weight	24.5 kg

### INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub), Video, S-Video, RCA
Digital input connector	DVI-D, HDMI
Audio-signal-input	PC-Audio, RCA L/R
Output connector	Audio, VGA (D-Sub), RS232C, Video
Inputs	RS232C
	D-Sub, DVI-D, HDMI

### SPECIAL FEATURES

Plug & Play	VESA DDC2BTM
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by side controls or a remote control
User controls	picture (picture mode, contrast, brightness, color, tint, sharpness, backlight, ACR, colour temperature), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H. position, V. position, ambient light sensor, auto detection), settings (language, schedule, display wall, power save, monitor ID, image retention, auto adjust, advanced), advanced settings (restore, OSD info box)
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV, CB
VESA mounting	400 x 200 mm
Colour	Black
Remote control	yes
Orientation	landscape

### ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Included accessories	power cable, D-Sub signal cable, remote control, iiyama logo sticker, quick start guide, safety guide