



ProLite C1911S-3

Prolite C1911S-3 is a 19" LED-backlit LCD display designed for demanding CCTV and Broadcast Applications. The 19" CCTV Display features a fast 5 m/s response time and a 1000:1 contrast ratio offering great colour performance with clear and vivid images. BNC and VGA inputs with and RCA Adapter included in the box ensure compatibility across multiple platforms, and VESA compliance allows for easy installation in any surveillance and security environment. This CCTV is also a real ECO-friendly product using LED-backlight which reduces the typical power consumption by approx. 20% in comparison to its predecessor.

DISPLAY CHARACTERISTICS

Diagonal	19"
Panel	TN LED-backlit
Display area h x w	301.06 x 376.32 mm; 11.9" x 14.8"
Response time	5 ms
Contrast	1000 : 1 typical
Brightness	250 cd/m² typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.294 x 0.294 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	30 - 82 KHz
Vertical sync	56 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	5 : 4

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	19 W typical; max. 1 W in Power management mode

DIMENSIONS & WEIGHT

Dimensions w x h x d	407 x 431.5 x 200.5 mm
Weight	3.9 kg

INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Output connector	AV (BNCx2)
Inputs	D-Sub, AV (BNCx2), Audio
	D-Sub

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2BT™
Controls	On-Screen-Display in 8 languages (EN, FR, DE, IT, ES, PT, NL, SE) and 5 Front controls (Power, Input Select/ Select, Scroll up, Scroll down, Meu/ Exit)
User controls	picture (brightness, contrast, colour, tint, sharpness, colour temperature), sound (bass, treble, balance, volume, audio source), option (OSD language, OSD timeout, AV switch, auto off, no signal off, reset), PC (auto adjust, H. position, V. position, clock, phase)
Speakers	2 x 1 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Safety	CE, TÜV/Bauart, CU
Tilt angle	20° up; 1° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista/ 7
Included accessories	power cable, D-Sub cable, BNC-RCA adapter, stand, quick start guide, safety guide