



ProLite E1706S

The 17" ProLite E1706S is one of the iiyama's New range of Eco Friendly products. With just a 19W typical power usage and as little as 1W in standby mode the monitor is an ideal choice for ECO-conscious consumers. By switching in the ECO Mode you can lower the power consumption even more and make sure the CO2 emission into the environment is considerably reduced. The ProLite E1706S delivers a sharp 20000:1 Advanced Contrast Ratio (ACR) and includes DVI and VGA connectivity. The monitor is available in Black.

DISPLAY CHARACTERISTICS

Diagonal	17"
Panel	TN
Display area h x w	270.3 x 337.9 mm; 10.6" x 13.3"
Response time	5 ms
Contrast	1000 : 1 typical
Contrast	20000 : 1 ACR
Brightness	250 cd/m² typical
Brightness	300 cd/m² max.
Viewing zone	horizontal/vertical: 170°/ 155°; right/left: 85°/ 85°; up/down: 75°/ 80°
Viewing zone CR>5	horizontal/vertical: 170°/ 170°; right/left: 85°/ 85°; up/down: 85/ 85°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	5:4

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	19 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

DIMENSIONS & WEIGHT

Dimensions w x h x d	371.5 x 382.5 x 190 mm
Weight	3.6 kg

INTERFACES & CONNECTORS

Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes
	D-Sub, DVI-D

SPECIAL FEATURES

SPECIAL FEATURES		
	Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
	Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, RU, JP, Chinese) and 5 front controls (Power, Menu/ Select Button, +/ Volume Button (+), -/ ECO Button (-), AUTO)
	User controls	luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position), colour adjust (gamma, colour temperature), OSD setup (H. position, V. position, timeout, language), others (reset, signal select, information), volume, auto adjust
	Speakers	2 x 1 W (Stereo)
A	nti-theft-device	Kensington-lock™ prepared
	Safety	CE, TÜV-GS, VCCI-B, TCO 6
	Tilt angle	20° up; 5° down
V	ESA mounting	100 mm
	Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Included accessories	Power Cable, D-Sub Cable, DVI-D Cable, Audio cable, user manual, stand