



ProLite E2473HS

The ProLite E2473HS LED-backlit monitor is a FHD (1920x1080) 24" display with high specifications, triple input connectivity (VGA, DVI and 2xHDMI) and fast 2ms response for excellent sharpness in high definition. VESA mount compatibility along with one HDMI input and headphone connector on the side of the cabinet ensure great comfort of usage and the X-Res Technology feature helps to deliver best quality pictures even if the source is not perfect, like movies made with mobile device.

DISPLAY CHARACTERISTICS

Diagonal	23.6"
Panel	TN LED-Backlit
Display area h x w	293.2 x 521.3 mm; 11.54" x 20.51"
Response time	2 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.2715 x 0.2715 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 82 KHz
Vertical sync	55 - 76 Hz
Synchronization	Separate sync
Aspect ratio	16 : 9

POWER MANAGEMENT

Power supply	AC100~240V 50/60Hz
Power Supply Unit	internal
Power usage	22 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

DIMENSIONS & WEIGHT

Dimensions w x h x d	556 x 418 x 218.5 mm
Weight	4.3 kg

INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D, 2 x HDMI
HDCP	yes
Headphone connector	Yes
Output connector	headphone connector D-Sub, DVI-D, HDMI

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2BTM
Controls	Via OSD in 8 languages (EN, DE, FR, NL, PL, Chinese, JP, RU) and 5 front controls (Power, Select/ Input Select, Scroll up/ X-Res technology, Scroll down/ i-Style Colour, Menu)
User controls	auto adjust, picture adjust (contrast, brightness, ACR, ECO, OD, X-Res Technology), input select, audio adjust (volume, mute, HDMI audio), colour adjust, information, manual image adjust (clock, H/V position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, opening logo, LED), memory recall
Speakers	2 x 2 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Certificates	CE, TUV-Bauart, VCCI-B, PSE, CU
Tilt angle	20° up; 0° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7 / 8
Included accessories	power cable, VGA (D-Sub) cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide