



## ProLite XB2779QS

**Sleek and stylish 27" AH-IPS LED-backlit screen with WQHD (2560 x 1440) resolution and a height adjustable stand**

Featuring WQHD (2560 x 1440) resolution, the XB2779QS can display almost 77% more information on the screen than a Full HD display. Users can create their own workspace by displaying and manipulating multiple applications at the same time. The AH-IPS matrix guarantees high performance with accurate and consistent colour reproduction, wide viewing angles and a fast response time. An array of inputs including HDMI, DisplayPort, DVI and VGA connections ensures compatibility across a wide range of multimedia devices. The XB2779QS is perfect for demanding users who settle only for the best specifications and modern design.

### DISPLAY CHARACTERISTICS

Diagonal	27"
Panel	AH-IPS LED-backlit
Display area h x w	335.7 x 596.7 mm; 13.2" x 23.5"
Response time	5 ms
Contrast	1 000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	350 cd/m <sup>2</sup> default, 440 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Display colour	16.77 million
Pixel pitch h x v	0.233 x 0.233 mm
Native resolution	2560 x 1440 ( 3.7 megapixel)
Horizontal sync	30 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Colour range	AdobeRGB: 86%, sRGB: 116%, 82% (NTSC)

### POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	55 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

### DIMENSIONS & WEIGHT

Dimensions w x h x d	650 x 435.5 (564.5) x 230 mm
Weight	8.2 kg

### INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D, HDMI, DisplayPort
HDCP	yes
Headphone connector	Yes
Output connector	headphone socket
	VGA, DVI-D, HDMI, DisplayPort

### SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2BTM
Controls	Via OSD in 9 languages (EN, FR, DE, NL, PL, RU, JP, Chinese (traditional and simplified)) and 5 front controls (Power, Select/ Input Select, Scroll up/ Volume, Scroll down/ i-Style Colour, Menu)
User controls	picture (brightness, contrast, ACR, ECO mode, OD), input select, audio (volume, mute, audio input), colour adjust, information, manual image adjust (H./V. position, clock, phase, sharpness, video mode adjust), setup menu (OSD setup menu, language, opening logo, LED, auto image adjust, memory recall)
Speakers	2 x 2 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Certificates	CE, TUV-Bauart, GOST-R, VCCI-B, PSE
Height adjustable stand	Yes
Height adjustment	130 mm
Swivel Stand	90°; 45° left; 45° right
Tilt angle	17° up; 0° down
VESA mounting	100 x 100 mm
Colour	Black

### ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7 / 8
Included accessories	power cable, DVI-D cable, DisplayPort cable, audio cable, stand, screws (x3), quick start guide, safety guide