

# SRK-MPPC Series

12"/15"/17"/19"  
Acero Panel PCS


**SRK-MPPC** series is an advanced acero Panel PC. Its ultra slim and exquisite metal enclosure catches most eye contacts. SRK-MPPC series includes four different display sizes, 12", 15", 17" and 19" equipped with high brightness TFT panel and resistive / SAW /IR touch. NEMA 4 / IP 65 dust and water proof display front meets industrial application requirements.

Beside standard model, SRK-MPPC series also derivate multiple different cabinet designs such as whole color painted sheet metal housing, complete stainless steel cabinet and panel mount model. Fanless and ventless or vandal proof design are also provided. For fitting different applications, SRK-MPPC series designs with desktop stand, MSR, laser scanner and camera kits.

SRK-MPPC series comprehensive product line is the best choice for digital signage, kiosk, e-home, KVS, healthcare, industrial automation, transportation, gaming and other applications.




## Features



1. Ultra slim, 60 mm thickness.



4. Rich I/O ports provide excellent peripheral connectivity.



2. Rugged metal housing and NEMA 4 / IP 65 dust & water proof display front.



5. 12", 15", 17" & 19" wide range display size.



3. Intel mobile technology supports multiple processors from Fanless ULV CPU to high performance Pentium M, core 2 dual.



6. Slim HDD bay design for easy service.

## SRK-MPPC Series



### Specification

Model Name	SRK792	SRK795	SRK797	SRK799
<b>Motherboard</b>	<b>B78</b>		<b>B98</b>	
CPU Supports	Intel Celeron M 1.3 / 1.5GHz; Pentium M 1.8GHz		Core Duo 2.0G / Core 2 Duo 2.16G	
Chipset	Intel 852GM and ICH4 FSB 400Mhz		Intel 945GME+ ICH7M	
System Memory	2 x DDR SO-DIMM slot, up to 2 GB		2 x DDRII SO-DIMM slot, up to 4 GB	
Graphic Memory	Share system memory max 64MB		Share system memory max 224MB	
<b>LCD / Touch Panel</b>				
LCD Size	12" TFT LCD	15" TFT LCD	17" TFT LCD	19" TFT LCD
Brightness	370nits	350nits	300nits	300nits
Maximal Resolution	800 x 600	1024 x 768	1280 x 1024	
Touch Screen Type	Resistive touch	Resistive type / SAW touch / IR Touch		
<b>Storage</b>				
HDD	2.5" Slim HDD bay			
Flash Memory	Optional Compact Flash memory (without HDD)			
<b>Expansion</b>				
mini-PCI Slot	1 x support 802.11 a/b/g WLAN card			
PCI express	1 for B98 main board only			
<b>External I/O Ports</b>				
USB 2.0	4 x USB Type A			
Serial / COM	RJ-45 (COM1 standard RS-232; COM2 RS-232 / 422 / 485 selectable by jumper; COM3 & COM4 pin 9 with 5V or 12V power by jumper)			
Parallel	1 x D-sub 25F			
LAN (10 / 100)	1 x RJ-45			
Cash Drawer	1 x RJ-11 (12V or 24V)			
DC Jack	1 x Latch Type			
Audio Jack	1 x MIC-in, 1 x Speak-out			
2nd VGA	1 x DB 15F			
<b>Internal Interface</b>				
USB 2.0	2			
<b>Audio</b>				
Speaker	1 x 3W Speaker	2 x 3W Speakers		
<b>Power</b>				
Power Adapter	DC 19V / 90W			
<b>Environment</b>				
EMC & Safety	FCC Class A, CE, LVD			
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)			
Storage Temperature	-20° ~ 60°C (-4°F ~ 140°F)			
Operating Humidity	5% - 95% RH non-condensing			
Storage Humidity	5% - 95% RH non-condensing			
Dust & Water Proof	NEMA 4 / IP 65 (front)			
<b>Dimension (W x D x H)</b>	331 x 265 x 55 mm 13" x 10.5" x 2.2"	386 x 308 x 60 mm 15.2"x 12.1"x 2.4"	411 x 345 x 60 mm 16.2" x 13.6" x 2.4"	449 x 374 x 60 mm 17.7" x 14.7" x 2.4"
<b>Weight</b>	N.W. 4.7kgs / 10.4 lbs	N.W. 5.8 kgs / 12.8 lbs	N.W. 7.6 kgs / 16.7 lbs	N.W. 9 kgs / 19.8 lbs
<b>Mounting</b>	100mm x 100mm Standard VESA / Panel Mount			
<b>OS Support</b>	Windows XP, WEPOS, XP Embedded, XP professional for Embedded, WIN 2000 professional Embedded, Linux			

Product specification subject to change without prior notice.