

Focus Firestore FS-CF Pro - Specifications

Display:	2.5 inch (diagonal) colour TFT display 320 x 240 pixel resolution
Input/Outputs:	DV I/O: 25Mbps HDV I/O: MPEG-2 transport stream (19.8 or 25 Mbps) Computer I/F: USB 2.0 (up to 48- Mbps) (1 x USB-A female) Video I/O: 1 x 6-pin IEEE 1394 (FireWire/i.LINK) RS-232C control: 1 x 2.5mm minijack
Audio DV input:	Embedded 2-channel (48 kHz, 16-bit) or 4-channel (32 kHz, 12-bit) NOTE: 4-channel (32 kHz, 12-bit) audio is supported only in DTE Technology with RawDV file format HDV input: Embedded MPEG-1 Audio Layer II
Video (DV):	25 Mbps; 8-bit 4:1:1 (NTSC-DV) or 4:2:0 (PAL-DV) (model dependent)
Video (HDV):	MPEG-2 (MP@H-14), 4:2:0, 720p (8-bit, 19.7 Mbps) or 1080i (8-bit, 25Mbps)
DTE Formats (HD):	.m2t 720p 24/25/30/50/60 .m2t 1080i 50/60 QuickTime 1080i 50/60 QuickTime 720p 30 MXF 1080i 50/60 MXF 720p 30
DTE Formats (SD):	AVI Type 1 AVI Type 2 AVI Type 2 24p QuickTime QuickTime 24p Canopus AVI Matrox AVI RawDV
Timecode:	DV embedded timecode (drop or nondrop)
Compact Flash Compatibility:	Records to industry-standard Compact Flash (CF) Type I cards, rated at minimum 30MB/s write speed.
Qualified CF Cards:	SanDisk Extreme Pro 64GB (90MB/s) SDCFXP-064G-A91 SanDisk Extreme Pro 32GB (90MB/s) SDCFXP-032G-A91 SanDisk Extreme Pro 16GB (90MB/s) SDCFXP-016G-A91 SanDisk Extreme 64GB (60MB/s) SDCFX-064G-A61 SanDisk Extreme 32GB (60MB/s) SDCFX-032G-A61 SanDisk Extreme 16GB (60MB/s) SDCFX-016G-A61 SanDisk Extreme 8GB (60MB/s) SDCFX-008G-A61 SanDisk Extreme IV 16GB SDCFX4-016G-901 Transcend 600X 32GB (90MB/s) TS32GCF600 Transcend 400X 64GB (90MB/s) TS64GCF400
Notes on Compatibility:	Please check with the CF manufacturer for up-to-date Part Numbers as changes may have occurred.
Disk Format:	UDF (Universal Disk Format) or FAT32 (user selectable)
OS Compatibility:	Windows XP, Vista, Windows 7, MAC OS X
Power Adapter:	11 - 18V DC; minijack power connector
Battery:	Custom removable Li-ion rechargeable battery
Battery Capacity:	Standard capacity battery (180 minutes)
Dimensions:	70 x 137 x 23 mm
Weight:	0.34 kg
Compliance:	CE, C-Tick, FCC, and RoHS
Warranty:	1 year
Models:	NTSC or PAL models available (PAL model ordered unless you state in the comments you want otherwise)