

Focus Firestore MR-HD100E – Specifications

- Display: 2.5-inch (diagonal) colour TFT LCD display
320- by 240-pixel resolution
- Input/Outputs: DV I/O: 25 Mbps
HDV I/O: MPEG-2 transport stream (19.8 or 25 Mbps)
Computer I/F: USB 2.0 (up to 480 Mbps) (1 x USB-A female)
Video I/O: 1 x 6-pin IEEE-1394 (FireWire/i.LINK)
GPI and RS-232C control (1 x 3.5mm minijack)
- Audio: DV input: Embedded 2-channel (48 kHz, 16-bit) or 4-channel (32kHz, 12-bit)
Note: 4-channel (12-bit, 32 kHz) audio is supported only in DTE Technology with RawDV file format
HDV input: Embedded MPEG-1 Audio Layer II
- Video (DV): 25 Mbps; 8-bit 4:1:1 (NTSC-DV) or 4:2:0 (PAL-DV) (model dependent)
- Video (HDV): MPEG-2 (MP@H-14) 720p (8-bit, 19.7 Mbps) or 1080i (8-bit, 25 Mbps)
- Timecode: DV embedded timecode (drop or nondrop)
- DTE Formats (SD): AVI Type 1, AVI Type 2, Canopus AVI, Matrox AVI, MXF, QuickTime, RawDV
- DTE Formats (HD): .m2t HDV (720p 24/25/30/50/60, 1080i 24/25/30/50/60)
MXF HDV (720p 30, 1080i 50/60)
QuickTime HDV (720p 30, 1080i 50/60)
- Disk: 120GB
- Disk Speed: 4200 RPM; 8MB cache
- Disk Format: UDF (Universal Disk Format) or FAT32
- Networking: USB 802.11 dongle
- OS Compatibility: Windows XP, Vista, Windows 7, Mac OS X
- Power Adapter: 11-18V DC; minijack power connector
- Battery: Custom removable Li-ion rechargeable battery
- Battery Capacity: Standard-capacity battery (180 minutes)
- Dimensions: 70 x 137 x 32 mm
- Weight: 0.34 kg
- Compliance: CE, C-Tick, FCC, and RoHS
- Warranty: 1 year
- Models: NTSC or PAL models available
(PAL model ordered unless you state in the comments you want otherwise)