

SRK-070-4

ADVERTISING DISPLAY (Panel Digital 7" con Player integrado y Lector de código de barras)



CARACTERISTICAS

El Lector (escáner) de código de barras se conecta por la parte trasera mediante miniDIN. Los videos de los productos que se quieran gestionar simplemente tiene que tener el "string" del código de barras como nombre del fichero de video en la tarjeta SD. No requiere ninguna programación. En cuanto el scanner lea el código de barras del producto reproducirá en un segundo el vídeo correspondiente.

El Lector de código de barras se compra como opción aparte.

- Supports multiple file formats: MP3, WMA, JPG, MPEG-1, MPEG-2, MPEG-4, VOB
- Supports CF/SD(High-speed), MMC/USB 2.0(Hot plug).
- Single repeat, All repeat.
- Auto-play when turned on with the cards/USB inserted; Supports 16 kinds of auto play
- Display mode: 4:3 / 16:9 (modificable)
- BGM mode (Auto-boot mode can be set): Support background music
- Pictures can be rotated 90°(Vertical display)
- Super time switch function, can auto turn on/off at a specific time
- One key copy; PC link is available
- Picture Display Time: Picture Display Time is modifiable
- Time Display: Time Display or not is modifiable
- Full function remote control, easy operation
- Multi-Language OSD: Chinese, English, Japanese, French, German, Danish, Spanish
- Product color: Pearl white, blue, black etc
- Accessories: Remote control(optional), instruction manual, AC adapter, bracket(optional)

ESPECIFICACIONES:

Display

LCD size:	7 inch (Diagonal)
Display area:	154.0x86.6mm 16:9
Resolution:	800*3(RGB)(W) X 480(H) (digital panel)
Pixel Pitch:	0.0642(W) × 0.1790(H) mm
Luminance:	250cd/m ²
Contrast Ratio:	500:1
Viewing Angle:	+70/-70 (H), +50/-70(V) (degree)
Response Time:	10ms
Display mode Optional	16:9 / 4:3
MTBF	50,000 (hours)

I/O

AC Power Input:	AC: 100~240 V
DC Power Output:	12V / 1.5A
Integrated Speakers:	2W x 2
IR Remote:	Yes
Menu OSD:	Yes

Card reader

Interface:	CF/MMC/SD/USB(2.0)
Photo:	JPEG, BMP
Video:	MPEG 1, MPEG 2, MPEG 4, AVI, MP4, VOB
Audio	MP3, WMA

Mechanical and Environmental

Operating temperature:	0°C~ 40°C (32°F~104°F)
Storage temperature:	-20°C ~60°C (-4°F~140°F)
Storage humidity:	10% ~ 95%@40°C,Non-condensing
External Colors:	Pearl white (other colors available, but MOQ: 200PCS)
Vibration:	10 ~ 150Hz, 0.15mm 10 cycles 1G
Shock:	30G peak acceleration (11 msec. duration)
Dimensions (L*W*H):	216.8 x 104.8 x 28mm non-include wall bracket

Accessories

Wall bracket:	Magnetic Bracket (Optional)(VESA 75mm/10 holes)
Remote control:	Yes (Infrared Remote) (Optional)
AC adapter:	Yes

Packing

Package:	10 PCS/CTN
Packaging Size/pcs:	28×26×10 cm (small white box)
Carton Size/10 pcs.	59.5×54×27.5 cm (carton)
Gross Weight:	1.5 kg/pcs

Conformity

Conformity:	CE, FCC, ROHS
Warranty:	1 Year