

## SMILSignage Display15

15,6" Widescreen HD Network Display



### Highlights

- ✓ 15.6" LCD for HD img/DVD-quality video
- ✓ VESA mountable integrated signage unit
- ✓ Works with your management solution

### Suitable for

- ✓ In-store promotion
- ✓ Interior décor integration
- ✓ Museum displays
- ✓ Library information system

SMILSIGNAGE DISPLAY15 Digital Signboard is a 15.6" widescreen, all-in-one digital signage display with dedicated digital signage features. The device is designed primarily for use with a management server.

### 15.6" LCD for HD images/DVD-quality video

The SMILSIGNAGE DISPLAY15 features a 300-nits, 15.6 inch wide aspect ratio high-definition LCD panel for displaying high definition images. Posters and information screen content appear razor-sharp with up to 1280x720 effective resolution. The built-in hardware-based video decoder is also capable of playing smooth DVD-quality MPEG-4 ASP videos up to 30 frames per second, enhancing the screen's flexibility in signage use.

### VESA mountable integrated signage unit

The SMILSIGNAGE DISPLAY15 integrates essential signage hardware and features in a VESA-mountable display unit. The compact unit integrates the media player, high brightness display, expandable local storage, and built-in Ethernet for easy placement. A watchdog timer lets the display recover and resume playback from power, network, or other disruptions. The custom enclosure provides reliable passive cooling and features screw-lock connectors to prevent loose cables. Covered SD card slot lets you expand beyond the 2GBs of built-in solid-state local storage while preventing removal of card. In addition to a built-in Ethernet port, the SMILSIGNAGE DISPLAY15 features built-in wireless b/g/n (2.4GHz only) networking to maximize installation options.

### Works with your management solution

Industry leading W3C SMIL supports paves the way for interoperable systems and efficient application development across a growing family of standards-compliant signboards and media player hardware.

HTML



POP AI  
THE GLOBAL ASSOCIATION FOR MARKETING AT RETAIL



## Technical Specifications

### Screen Media Standards Support

Image: JPEG baseline profile, up to 12 megapixels (1280x720 optimum)

Audio: MPEG L2 or MP3, up to 320Kbps

Video: MPEG-1 or MPEG-4 ASP, 2Mbps (720x400 optimum)

NOTE: MPEG-2 video must be transcoded to MPEG-4 ASP for playback

### Digital Signage Features

Auto-play starts playing scheduled contents automatically when power is re-established

Automatic error recovery with built-in WDT

Real-time clock battery keeps time for up to 2 years unplugged

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

Automatic NTP keeps time and date in sync

### Display and Sound

15.6" 16:9 TFT LCD panel

300 nits maximum brightness

1366x768 panel resolution

Built-in stereo speakers 2Wx2

### Local Storage

Internal 2GB local storage (approx. 120

minutes of maximum quality video @2Mbps

or thousands of still images)

Memory card slot: Secure Digital

(SD/SDHC)

Card capacity: up to 8GB (SDHC)

### Physical I/O Connectors

Ethernet: RJ45 Port

Wi-Fi: IEEE 802.11 b/g/n (2.4GHz only)

3.5mm Audio out

USB host (Type A) x1

### Mounting Options

VESA MIS-D75 mounting posts

### Accessories

Power adapter

Ethernet cable

Wi-Fi antenna

Monopod flex stand

(Optional) PVK-202 VESA display stand

### Power supply

Rating: 12V / 3.3A

UL/PSE (Japan) certified

### Power consumption

24 Watts (video playback at 100%

brightness)

### Environmental

Operating temperature: 0 to 40°C

Humidity: 5 to 85% @ 40°C, non-

condensing

### Dimensions

Main body (WxHxD): 382 x 253 x 54 mm /

15" x 10" x 2.13"

### Weight


2.65 Kg / 5.84 pounds

### Certifications

CE/FCC/RoHS

### Warranty

1-year limited parts & labor



Sirkom Europe, S.L.  
 Avda. Lendakari Aguirre, 50-52 – 48014 Bilbao (Spain) Tel. +34 944765344  
 marketing@sirkom.com